



-005 STRAP

2 2.	METAL TO 230 HOLE	BE PERFORATE S PSI 37% O/A	D .045" DIA.	STRAIGHT	LINE CTRS
-------------	----------------------	-------------------------------	--------------	----------	-----------

DRILL & TRIM STRAP TO MATCH FAIRING & LUG ON INSTALLATION.

NOTES:

-001 STRAP

NO. REQ'D PER	ASSY.	-005 -003 -001 PART NO.		STRAP STRAP STRAP NAME	2 x 6 9.0x 3.2 6.x 1. STOC OF MATERIA	25x.024 x.024 K SIZE	24 GA. TYPE 304 STLS. STL 24 GA TYPE 316 STLS. STL 24 GA. TYPE 304 STLS. STL 24 GA. TYPE 316 STLS. STL 24 GA. TYPE 316 STLS.—STL 24 GA. TYPE 316 STLS.—STL 24 GA. TYPE 316 STLS.—STL	1/4 HARD QQ-S-766 (A) 1/4 HARD MIL-S-5059 (B) 1/4 HARD QQ-S-766 (A)
THE FOREGOING DOES	~ I	11228-203-049 11228-203-049 NEXT ASSEMBLY	MOs.	OTHERWISE SPECIFIED (ORFTSMIN T. HAF CHECK STRESS ROJ. ENGR. EAT TREAT	RVILLE	7/19/93 TITLE GROUN DWG. SIZE CO-	DWG. NO. REV.

-.12 R. TYP.

1.0

-003 STRAP

:O: